

Pulisol

PROFESSIONAL SCENTED DEGREASING DETERGENT IN BASE SOLUTION, GUARANTEED FOR NON-AGGRESSIVE CLEANING OF COMPACT SURFACES FOULED WITH GREASE, OIL, WAX SUBSTANCES. ESSENTIAL BEFORE OVERLAYING AN EXISTING FLOOR.



TECHNICAL DATA SHEET - REV. 01/2023

DESCRIPTION

PULISOL is a degreasing detergent consisting of alkaline surfactants and other additives, used for the non-aggressive cleaning of compact surfaces soiled with greasy substances, oils, waxes.

FIELDS OF APPLICATION

PULISOL is used to remove dirt caused by oils, atmospheric pollution or smog from glazed tiles, single-fired tiles, klinker, porcelain stoneware, glass mosaics, terracotta or to remove smog from concrete surfaces, marble, sandstone. Do not use on polished and composite marble.

APPLICATION

Before cleaning with PULISOL, it is necessary to protect everything that can be damaged from possible splashes of product. Apply PULISOL with a brush or roller and leave it on for about 5 minutes. Brush and reapply the product to the traces or persistent stains. Wash thoroughly with warm water, preferably under pressure.

YIELD

150-200 g/m² depending on the condition of the surface.

RECOMMENDATIONS

- ◆ Before use, it is always advisable to carry out preliminary tests to ensure that the surface to be cleaned will not deteriorate.
- ◆ Use at least one week later after grouting the joints.
- ◆ Never use PULISOL on shiny aluminium, zinc or marble.
- ◆ PULISOL is an alkaline product. Avoid contact with skin and eyes; wear protective gloves, goggles and shoes.

PACKAGING

PULISOL is supplied in 5 kg plastic cans on 450 kg pallets. Store the product in a dry place and in its original packaging, well closed and protected from frost. In these conditions its stability lasts at least 12 months.

SAFETY INSTRUCTIONS

Refer to the respective Safety Data Sheet for more information about how to use the product safely.

SPECIFICATIONS

Professional scented degreasing detergent in alkaline solution, such as **PULISOL** by Colmef Srl, for non-aggressive cleaning of compact surfaces soiled with greasy substances, oils, waxes. indispensable before overlaying on an existing floor.

TECHNICAL DATA

Appearance:	liquid
Colour:	transparent
Apparent specific weight (kg/l):	1.00
pH:	13.5
Waiting time before rinsing:	15 min.
Allowed application temperature:	from -5 °C to +35 °C

DATA DETECTION AT +23°C - 50% R.H. AND IN ABSENCE OF VENTILATION

The information in this bulletin is based on our best experience. We cannot be held liable for any product misuse. We therefore recommend anyone who intends to use this product to assess whether it is suitable for the intended application and to perform preliminary tests in any case. Always refer to the latest updated version of the technical data sheet available at www.colmef.com.

FOR MORE INFORMATION OR PARTICULAR USES, CONTACT THE COLMEF TECHNICAL SUPPORT DEPARTMENT.

COLMEF SRL | Z.I. Ponte d'Assi | 06024 - Gubbio (PG) ITALY | Tel. +39 075923561 | info@colmef.com | www.colmef.com